bollé sacty

Featured In:

1652801A • Clear Lens Indirect Vents
Top & Bottom

1652821A • Clear Lens Top Vent Closed

1652831A • Clear Lens Indirect Vents Top and Bottom w/Mouthguard

Accessories:

1650015 • RX Adaptor



1652801A



1652831A

atom

Applications:

- Chemical splash protection
- Cutting
- Spraying
- Dust protection
- Acid and alkaline handling
- Wood and metal work

Technical Specifications: Frame

Soft, comfortable PVC frame contours to your face for a great seal & fit

Lenses

- 'ALS' anti-fog / anti-scratch coating on both sides of the Clear lens
- 100% UV 385 Clear

Main Markets:

- Petro Chemical
- Construction
- Manufacturing
- Paint
- Automotive
- Labs

Weight:

72 Grams

Standards:

Approved to ANSI Z87.1-2010 for High Impact Protection.

Cleaning Instructions:

Bollé Safety recommends only using our **ECLERN** Lens cleaning system to clean our products.

Features & Benefits:

- Low profile and lightweight frame with a spherical polycarbonate lens
- 'ALS' anti-fog/anti-scratch coating on both sides of the Clear lens
- Spherical lens offering brilliant peripheral vision
- **Highlight Feature:** Asian nose bridge